




**PRODUCT: - POLYSTER FABRIC SINGLE TEXTURE ONE SIDE NEOPRENE RUBBER & OTHER SIDE HYPALON RUBBER COATED FABRIC TECHNICAL DATA SHEET**



**TECHNICAL SPECIFICATION**

SR NO	PROPERTY	UNIT	STANDARDS	SPECIFICATION
1	Product Code	..	...	GAS BALOON COATED FABRIC
2	Coated Fabric Thickness	MM	IS 7016 - PART I	1.20 ± 0.10
3	Coated Fabric GSM	Gram/sq. meter	IS 7016 - PART I	1500 ± 100
4	Coated Fabric Width	CMS OR MM	IS 7016 - PART I	140
5	<b>BREAKING STRENGTH</b>			
A)	Warp	Kg/50mm	IS 7016 - PART II	500
B)	Weft	Kg/50mm	IS 7016 - PART II	450
6	<b>ELONGATION AT BREAK</b>			
A)	Warp	Kg/50mm	IS 7016 - PART II	24 ± 6
B)	Weft	Kg/50mm	IS 7016 - PART II	26 ± 6
7	<b>TEAR STRENGTH</b>			
A)	Warp	Kg/50mm	IS 7016 - PART III	25
B)	Weft	Kg/50mm	IS 7016 - PART III	25
8	<b>PEEL SARENGTH</b>			
A)	Warp	Kg/50mm	IS 7016 - PART V	5 KG
B)	Weft	Kg/50mm	IS 7016 - PART V	5 KG
9	Colour		As Per Required	As Per Customer Requirement
10	Air Leak Test	Gms/Cm2	As Per Required	When tested at a pressure of 400 gms/cm2 - no leakage found
11	Polymer	..	As Per Required	Neoprene Rubber Hypalon Rubber

**Note:** All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.\*

