


# Abra-Skirt 65

## PRODUCT CODE – Abra-Skirt 65



### TECHNICAL SPECIFICATIONS

| PROPERTIES                           | TEST METHOD | VALUES          | TEST METHOD | VALUES           |
|--------------------------------------|-------------|-----------------|-------------|------------------|
|                                      |             | FPS UNITS       |             | FPS UNITS        |
| SPECIFIC GRAVITY                     | -           | 1.35 ± 0.05     | ASTM D297   | 1.35 ± 0.05      |
| HARDNESS                             | ISO 48-4    | 65 ± 5 Sh A     | ASTM D2240  | 65 ± 5 Sh A      |
| TENSILE STRENGTH ( min )             | ISO 37      | 853 PSI         | ASTM D412   | 60 kg/cm 2       |
| ELONGATION AT BREAK ( min )          | ISO 37      | 300 %           | ASTM D412   | 300 %            |
| TEAR RESISTANCE ( Angular ) min      | ISO 34-1    | 112 Lbs/Inch    | ASTM D624   | 20 Kg/cm         |
| CHANGE IN PROPERTIES AFTER           |             |                 |             |                  |
| HEAT AGEING FOR ( 72 hrs. AT 70 °C ) |             |                 | ASTM D573   |                  |
| --- HARDNESS (Pts)                   |             | + 5 (Max)       |             | + 5 (Max)        |
| --- TENSILE STRENGTH (%)             |             | + 10 / - 25     |             | + 10 / - 25      |
| --- ELONGATION AT BREAK (%)          |             | + 10 / - 25     |             | + 10 / - 25      |
| VOLUME SWELL : AT 70°C FOR 72 HRS    |             |                 | ASTM D 471  |                  |
| IN IRM OIL NO.901                    |             | NOT RECOMMENDED |             | NOT RECOMMENDED  |
| IN IRM OIL NO.902                    |             | NOT RECOMMENDED |             | NOT RECOMMENDED  |
| IN IRM OIL NO.903                    |             | NOT RECOMMENDED |             | NOT RECOMMENDED  |
| CHEMICAL RESISTANCE                  |             |                 |             |                  |
| --- OZONE                            |             | NOT RECOMMENDED | ASTM D 1149 | NOT RECOMMENDED  |
| --- DILUTE ACIDS AND BASES           |             | NOT RECOMMENDED |             | NOT RECOMMENDED  |
| --- CONCENTRATED ACIDS AND BASES     |             | NOT RECOMMENDED |             | NOT RECOMMENDED  |
| --- OILS                             |             | NOT RECOMMENDED |             | NOT RECOMMENDED  |
| --- SOLVENTS                         |             | NOT RECOMMENDED |             | NOT RECOMMENDED  |
| TEMPERATURE RANGE                    |             | -30° to + 70° C |             | -30 ° to + 70° C |
| COLOR                                |             | BLACK           |             | BLACK            |

Note: All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.\*

